

STUDIOMASTER T700 Turntable - BLACK EDITION -

High-end turntable with a unique integrated MC phono preamplifier. Highprecision electronic PLL speed control with contact-free optical sensor. Control panel with backlit touch sensors. Tonearm made of high-grade metals.

In the - **BLACK EDITION** - exclusively equipped with the high-quality MC pickup *Ortofon Quintet Black S*.

The top system of the Quintet series

The Quintet Black S is graced with a Nude Shibata diamond, considered one of the best stylus profiles available, mounted on a high-performance Sapphire cantilever. The Shibata's slim, highly polished profile allows an exceedingly wide contact area to the walls of the groove and ensures detailed and pure reproduction throughout the spectrum, including even the most high frequency groove information.



STUDIOMASTER T700 Turntable - BLACK EDITION -



Ortofon MC Quintet Black S

TECHNICAL DATA

|                       |  |                   |   |
|-----------------------|--|-------------------|---|
| Order Number          | 1.279.006.00   | Pick-up           | Ortofon MC Quintet Black S  |
|                       | MC Phono Preamplifier                                | Speed             | 33 / 45 revolutions per minute  |
| Frequency response    | 7 Hz ... 80 kHz (-3dB)                               | Speed variation   | < 0.1%  |
| Signal-to-noise ratio | - 69 dB (20 Hz ... 20 kHz)                           | Connectors        | Analogue line output (cinch stereo)<br>DC power socket                      |
| Distortions           | 0,005 %  | Dimensions        | 470 x 336 x 156 mm (WxDxH) without sockets                                  |
| Channel offset        | 0.2 dB   | Projection (back) | 16 mm (hinge, RCA sockets)  |
| Channel separation    | higher 80 dB   | Weight            | 10.3 kg total<br>2.85 kg platter (POM)<br>0.21 kg inner platter (aluminium) |
| Subsonic filter       | 10 with first-order high pass<br>(6 dB filter)       |                   |   |
| RIAA precision        | ± 0.2 %  |                   |   |
| Impedance matching    | 6 settings: 47 Ω, 100 Ω, 220 Ω,<br>470 Ω, 1 kΩ, 2 kΩ |                   |   |
| Input sencitivity     | 4 settings: 150 μV, 300 μV,<br>600 μV, 1,2 mV        |                   |   |

ACCESSORIES

|                                      | incl. |
|--------------------------------------|-------|
| Solid acrylic glass protective cover | ✓     |
| Digital tonearm scale                | ✓     |
| Record brush                         | ✓     |
| Bubble level                         | ✓     |
| Anti-skating weight                  | ✓     |
| Tonearm counterweight                | ✓     |
| Turntable belt                       | ✓     |
| White gloves                         | ✓     |



Accessories in a noble wooden box (incl.)